



High Density

Medium Density

Standard Density

Economy Tape

Stock Code	Container Size	Units per Case
TT23	3/4" x 288"	24
TT33	3/4" x 576"	24
TT38	3/8" x 520"	144
TT40	1/2" x 260"	144
TT41	1/2" x 520"	144
TT42	1/4" x 520"	144
TT43	1/4" x 260"	144
TT44	1/2" x 1296"	144

Stock Code	Container Size	Units per Case
TT54	3/4" x 520"	24
TT60	1/2" x 260"	144
TT61	1/2" x 520"	144

Stock Code	Container Size	Units per Case
ZT12	3/4" x 260"	100
ZT13	3/4" x 500"	100
ZT15	3/4" x 520"	100
ZT20	1/2" x 260"	144
ZT20-BC	1/2" x 260"	24
ZT21	1/2" x 520"	144
ZT51	1" x 520"	100

Stock Code	Container Size	Units per Case
1901C	1/2" x 260"	100
1901C-BC	1/2" x 260"	24
1901D	1/2" x 520"	100
1901E	3/4" x 520"	100
1901F	1" x 520"	50
1901G	1" x 1296"	140

- All virgin PTFE
- Temperature range: -450°F to 550°F (-268°C to 288°C)
- Use up to 10,000 PSI for liquids, 2,000 PSI for gases

- All virgin PTFE
- Temperature range: -450°F to 550°F (-268°C to 288°C)
- Use up to 10,000 PSI for liquids, 2,000 PSI for gases

- All virgin PTFE
- Temperature range: -450°F to 550°F (-268°C to 288°C)
- Use up to 10,000 PSI for liquids, 2,000 PSI for gases

- All virgin PTFE
- Temperature range: -450°F to 550°F (-268°C to 288°C)



Zip Joint® Rope Gasket Maker

Stock Code	Container Size	Units per Case
ZJ11	3/32" Dia. x 25' Coil	6
ZJ13	5/32" Dia. x 25' Coil	6

- Ideal for packing valves and faucets; use on garden hoses, laundry hoses, shower heads and more
- Quickly makes any gasket
- Simple and clean installation
- Spreads under compression to conform to odd shapes
- Sealing agent withstands vibration
- Unique package allows for easy dispensing and storage
- Temperature Range: -450°F to 550°F (-268°C to 288°C)
- Pressure Range: To 500 PSI (34 bar) under general use

Density Type	HD	MD	SD
	High	Medium	Standard
Thickness (mils)	3.9	3.5	3.5
Tensile (Min *psi)	800	800	800
UL Listed	Yes	No	No
MIL SPEC*	AA-58092	AA-58092	AA-58092
MIL SPEC*	27730A	27730A	27730A
Density (g/cm³)	0.9 - 1.2	0.8 - 1.05	0.5 - 0.9
Elongation (%)	50	50	50
Temp. Range (°F)	-450 to +550	-450 to +550	-450 to +550
Shelf Life	Indefinite	Indefinite	Indefinite

*Meets Performance Requirements of Mil Specifications Listed.

PTFE TAPE SPECIFICATIONS



Green For Oxygen

Stock Code	Container Size	Units per Case
GT90-24	1/2" x 260"	24
GT90	1/2" x 260"	144

- Designed for sealing oxygen based lines
- Use on all types of threaded connections
- Meets Mil Spec MIL-AA-58092
- Temperature range: -450°F to 550°F (-268°C to 288°C)
- Use up to 10,000 PSI for liquids 2,000 PSI for gases



Yellow For Gas

Stock Code	Container Size	Units per Case
YT70-24	1/2" x 260"	24
YT70	1/2" x 260"	144
YT71	1/2" x 520"	100
YT75	1" x 520"	100

- Designed for chemical installations and sealing lines carrying natural gas, propane, butane and oil
- Meets MIL Spec MIL-AA-58092
- Temperature range: -450°F to 550°F (-268°C to 288°C)
- Use up to 10,000 PSI for liquids 2,000 PSI for gases



Pink For Water

Stock Code	Container Size	Units per Case
PT80-24	1/2" x 260"	24
PT80	1/2" x 260"	144

- Designed for sealing water and/or steam lines
- Use on all types of threaded connections
- Meets Mil Spec MIL-AA-58092
- Temperature range: -450°F to 550°F (-268°C to 288°C)
- Use up to 10,000 PSI for liquids 2,000 PSI for gases



Nickel For Stainless Steel

Stock Code	Container Size	Units per Case
SA26	1/2" x 260"	40
SA26-34	3/4" x 260"	40
SA520-1	1" x 520"	40
SA260-1	1" x 260"	40
SA60	1/2" x 600"	50

- Designed for use on difficult service conditions associated with stainless steel, aluminum and brass threaded connections
- Helps prevent seizing and galling
- NOT for use with oxygen
- UL® Listed thread sealant
- NSF/ANSI 51 Listed thread sealant
- Meets Mil Spec MIL-T-27730A
- Temperature range: -450°F to 550°F (-268°C to 288°C)
- Use up to 10,000 PSI for liquids 2,000 PSI for gases



PTFE TAPE SPECIFICATIONS

	Yellow	Pink/Green	Stainless
Density Type	High	High	High
Thickness (mils)	3.8	3.7	4.3
Tensile (Min *psi)	1600	1600	1600
UL Listed	Yes	Yes	Yes
MIL SPEC*	AA-58092	AA-58092	AA-58092
MIL SPEC*	27730A	27730A	27730A
Density (g/cm3)	1.3 - 1.45	1.25 - 1.55	1.25 - 1.55
Elongation (%)	75	75	75
Temp. Range (°F)	-450 to +550	-450 to +550	-450 to +550
Shelf Life	Indefinite	Indefinite	Indefinite

*Meets Performance Requirements of Mil Specifications Listed.



FEDPRO
TRUSTED BRANDS SINCE 1915